



Designed,
Developed &
Manufactured In India



TCX200 – 4S / 8S / 11S

PBX Solution for Small & Medium Enterprises



Extension Features

- Abbreviated Class Of Service
- **Auto Call Back**
- Call Forwarding
- Call Hold
- Call Park & Retrieve
- Call Pickup
- Call Transfer
- Call Camp On
- **Conference (Three to Five)**
- Dynamic Lock(With Auto Shut Lock)
- **Emergency Extension**
- Hotline (Delayed/Undelayed)
- Feature Access Level Programming
- Department Call
- **Do Not Disturb**
- Intrusion
- Specific Line Access
- **Last Number Redial**
- **Paging (External/Internal)**
- Remainder Service
- Marked Call
- Night Guard Service
- **Speed Dial**
- Missed Call
- Last Attended Call Back
- **Interrupt Request**
- Follow Me

Special Features

- **Daily Alarm**
- Alarm Reminder –Remote
- Auto Call Disconnection
- **Auto Night Mode Changeover**
- Class Of Service
- Call Budgeting
- Caller Identification
- Cyclic Line Access
- Denied Table
- **DISA & DOSA**
- Distinctive Ringing
- **External Call Forward**
- Flexible Numbering
- **Account Code**
- Line Access Groups
- Walking Class of Service
- Forcible Disconnection
- Meet Me Conference
- Trunk Based Denied Table
- Polarity Reversal Detection
- Auto Dialing For Missed Call
- **Speed Zone Programming**
- Incoming Ringing Sequence Assignment
- Music On Hold
- Extension Group
- Power Failure Mode
- **Remote Programming**
- SMDR
- Trunk Flashing
- Tone/Pulse Dialing
- Add On Conference
- **Flexible Voice Recording**
- Trunk to Trunk Patch up
- Deny Beyond Free Calls
- Trunk Reservation
- **CLI Based Routing**
- Delayed DID
- **Auto - Attendant**
- LAN Connectivity
- **Flat door lock**
- **Multiple paging**
- Self Number Check
- Self Ring Check
- **Voice Prompt for Ext. Number**
- **Voice Prompt for Port Number**
- **Talking Caller ID**

System Features

- Caller-ID (Both DTMF & FSK)
- Over Voltage Protection
- Inbuilt Lightning Arrester
- Attractive Metal Cabinet
- Flexible Mounting Option: Wall Mount / Desktop
- Direct Trunk Access During Power Failure
- Surge Current Protection
- Trunk LED Monitor

KTS Features


- 24 Prog. Flex Keys
- On Hook Keypad Dialing
- Call Queuing
- Call Indication Lamp
- Extension Redial
- Calling Number Display
- Hands Free Operation
- Room Monitor
- Busy Lamp Indication
- Mute
- Multiple Call Hold
- Do Not Disturb
- Conference(three to five)

Hotel Features

- Wake Up Alarm
- Service Extension Single Digit
- Room to Room Call Restriction
- Call Accounting Software Integration
- Toll Restriction

Technical Specification

	TCX200-4S	TCX200-8S	TCX200-11S
Ext. (Max.)	2-KTS + 32 / 2-KTS + 48	2-KTS + 96	2-KTS + 128
Trunk (Max.)	8/4	8	8
AC Voltage	230V / 50Hz	230V / 50Hz	230V / 50Hz
Power Consumption	72W (Max.)	72W (Max.)	72W (Max.)
Ext. Voltage	28Vdc	28Vdc	28Vdc
Ringer Voltage	65Vac	65Vac	65Vac
Dimension	435*255*105mm	360*267*192mm	435*267*192mm
Environment	0 °to+45 °C, 20% to 80% Humidity	0 °to+45 °C, 20% to 80% Humidity	0 °to+45 °C, 20% to 80% Humidity



Talking Caller ID



Caller-ID



Conference



Call Back



Daily Alarm



Paging