308FX-A

FSK SUPPORTABLE PBX



System Features

- Caller-ID Detection[FSK & DTMF]
- Over Voltage Protection
- Inbuilt Lightning Arrester
- Attractive Metal Cabinet
- Flexible Mounting Option: Wall Mount / Desktop
- Power Failure Transfer
- Surge Current Protection
- Trunk & Extension LED Monitor

Extension Features

- Making an Intercom Call
- Making an Outside Call
- Holding a Call
- Camped Call
- Auto Call Back
- Call Camp On
- Call Follow Me
- Call Forward Anytime
- Call Forward During Busy
- Call Transfer While Ringing
- Call Transfer with Consult
- Trunk Waiting Call Pickup
- Emergency Reporting
- Flexible Numbering
- Remote Programming
- Call Parking
- Parked Call pickup
- Trunk Grouping
- Trunk Allocation
- Trunk Redial
- Direct Inward Dialing
- Paging
- Hot Line [Delayed/Undelayed]
- Conference
- Do Not Disturb
- Call Pickup
- Call Privacy
- Call Split
- Broker Call
- Barge-in
- Feature Cancellation
- Global Memory Dialing [100Nos]
- Least Cost Routing
- Room to Room Calling
- Voice Guidance [optional]
- Manual day night change over
- Executive Extension
- Denied Table

Technical Specification

Trunk	3
Extension	8
Input	150 - 240Vac 50/60 Hz
Power Consumption	24W (Max.)
Extension Voltage	28Vdc
Ringer Voltage	50 - 75Vac
Dimension	243*187*57 mm
Environment	0 °to +45°C, 20% to 80% Humidity




Caller-ID



Conference



Call Back



Auto Attendant



Paging