Designed, Developed &
Manufactured In India

Telematics

416FX-A

FSK SUPPORTABLE PBX



System Features

- Caller-ID Detection[FSK&DTMF]
- Over Voltage Protection
- Inbuilt Lightning Arrester
- Attractive Metal Cabinet
- Flexible Mounting Option: Wall Mount/Desktop
- Power Failure Transfer
- Surge Current Protection
- Trunk & Extension LED Monitor

Extension Features

- Making an Intercom Call
- Making an Outside Call
- Holding a Call
- Camped Call
- Auto Call Back
- Call Camp On
- Call Follow Me
- Call Forward Anytime
- Call Forward During Busy
- Call Transfer While Ringing
- Call Transfer with Consult
- Trunk Waiting Call Pickup
- Emergency Reporting
- Flexible Numbering
- Remote Programming
- Call Parking
- Parked Call pickup
- Trunk Grouping
- Trunk Allocation
- Trunk Redial
- Direct Inward Dialing
- Paging
- Hot Line[Delayed/Undelayed]
- Conference(3PartyConference)
- Do Not Disturb
- Call Pickup
- Call Privacy
- Call Split
- Broker Call
- Barge-in
- Feature Cancellation
- Global Memory Dialing[100Nos]
- Least Cost Routing
- Room to Room Calling
- Manual day night changeover
- Executive Extension
- Denied Table

Technical Specification

Trunk	4
Extension	16
Input	90-265Vac50/60Hz
Power Consumption	60W(Max.)
Extension Voltage	28Vdc
Ringer Voltage	50-75Vac
Dimension	320*210*55mm
Environment	0°to+45°C,20%to80% Humidity

GeM Government e Marketplace

Caller-ID | Conference | Call Back | Auto Attendant | Paging