



Designed,
Developed &
Manufactured In India



104FX-A

FSK SUPPORTABLE PBX



System Features

- Caller-ID Detection[FSK & DTMF]
- Over Voltage Protection
- Inbuilt Lightning Arrester
- Attractive Metal Cabinet
- Flexible Mounting Option: Wall Mount / Desktop
- Power Failure Transfer
- Surge Current Protection
- Trunk & Extension LED Monitor

Extension Features

- Making an Intercom Call
- Making an Outside Call
- Holding a Call
- Camped Call
- **Auto Call Back**
- Call Camp On
- Call Follow Me
- Call Forward Anytime
- Call Forward During Busy
- Call Transfer while Ringing
- Call Transfer with Consult
- Trunk Waiting Call Pickup
- Emergency Reporting
- **Flexible Numbering**
- Remote Programming
- **Call Parking**
- **Call Blocking**
- Trunk Redial
- Direct Inward Dialing
- Paging
- Hot Line
- **Conference**
- Do Not Disturb
- Call Pickup
- Call Privacy
- Call Split
- Broker Call
- **Barge-in**
- Feature Cancellation
- **Global Memory Dialing (100 Nos)**
- Executive Extension
- Parked Call pickup

Technical Specification

Trunk (Max.)	1
Extension (Max.)	4
AC Voltage	230V / 50Hz
Power Consumption	24W (Max.)
Extension Voltage	28Vdc
Ringer Voltage	75Vac
Dimension	220*140*40mm
Environment	0 ° to +45 °C, 20% to 80% Humidity



Call Blocking




Caller-ID



Conference



Call Back



Auto Attendant



Paging