



Designed,  
Developed &  
Manufactured In India



# 206FX-A

## FSK SUPPORTABLE PBX



### System Features

- Caller-ID Detection[ FSK & DTMF ]
- Over Voltage Protection
- Inbuilt Lightning Arrester
- Attractive Metal Cabinet
- Flexible Mounting Option: Wall Mount / Desktop
- Power Failure Transfer
- Surge Current Protection
- Trunk & Extension LED Monitor

### Extension Features

- Making an Intercom Call
- Making an Outside Call
- Holding a Call
- Camped Call
- Auto Call Back
- Call Camp On
- Call Follow Me
- Call Forward Anytime
- Call Forward During Busy
- Call Transfer While Ringing
- Call Transfer with Consult
- Trunk Waiting Call Pickup
- Emergency Reporting
- Flexible Numbering
- Remote Programming
- Call Parking
- Parked Call pickup
- Trunk Grouping
- Trunk Allocation
- Trunk Redial
- Direct Inward Dialing
- Paging
- Hot Line[ Delayed / Undelayed ]
- Conference(3 Party Conference)
- Do Not Disturb
- Call Pickup
- Call Privacy
- Call Split
- Broker Call
- Barge-in
- Feature Cancellation
- Global Memory Dialing[ 100 Nos ]
- Least Cost Routing
- Room to Room Calling
- Manual day night change over
- Executive Extension

### Technical Specification

Trunk	2
Extension	6
Input	90 - 265Vac 50/60 Hz
Power Consumption	24W (Max.)
Extension Voltage	28Vdc
Ringer Voltage	50 - 75Vac
Dimension	236*134*40 mm
Environment	0 ° to +45 °C, 20% to 80% Humidity




Caller-ID



Conference



Call Back



Auto Attendant



Paging